

Cassette Type Indoor Unit



Built-in drain pump



Washable filter



Quiet function



Compact design



Easier maintainability

4-way Cassette

Model			GMV-Rh28T/Na-K	GMV-Rh36T/Na-K	GMV-Rh45T/Na-K	GMV-Rh50T/Na-K	GMV-Rh56T/Na-K	GMV-Rh63T/Na-K	
Capacity	Cooling	kW	2.8	3.6	4.5	5.0	5.6	6.3	
	Heating	kW	3.2	4.0	5.0	5.8	6.3	7.0	
Power supply	PhV/Hz		1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	
Motor power input	W		65	65	65	65	83	83	
Air flow volume	m³/h		680	680	680	680	1180	1180	
	CFM		400	400	400	400	694	694	
Sound pressure level	dB(A)		37/35/33	37/35/33	37/35/33	37/35/33	39/37/35	39/37/35	
Main body	Dimension (WxDxH)	Outline	mm	840×840×190	840×840×190	840×840×190	840×840×190	840×840×240	840×840×240
		Package	mm	1103×963×272	1103×963×272	1103×963×272	1103×963×272	1103×963×325	1103×963×325
	Net weight/Gross weight		kg	25/33	25/33	25/33	25/33	30/38	30/38
Panel	Dimension (WxDxH)	Outline	mm	950×950×60	950×950×60	950×950×60	950×950×60	950×950×60	950×950×60
		Package	mm	1043×1028×130	1043×1028×130	1043×1028×130	1043×1028×130	1043×1028×130	1043×1028×130
	Net weight/Gross weight		kg	6.5/10	6.5/10	6.5/10	6.5/10	6.5/10	6.5/10
Connecting pipe diameter	Gas	inch(mm)	φ3/8(9.52)	φ1/2(12.7)	φ1/2(12.7)	φ1/2(12.7)	φ5/8(15.9)	φ5/8(15.9)	
	Liquid	inch(mm)	φ1/4(6.32)	φ1/4(6.32)	φ1/4(6.32)	φ1/4(6.32)	φ3/8(9.52)	φ3/8(9.52)	
Loading quantity	40'GP	set	112	112	112	112	100	100	
	40'HQ	set	124	124	124	124	114	114	

Model			GMV-Rh71T/Na-K	GMV-Rh80T/Na-K	GMV-Rh90T/Na-K	RGMV-h100T/Na-K	GMV-Rh112T/Na-K	GMV-Rh125T/Na-K	
Capacity	Cooling	kW	7.1	8.0	9.0	10.0	11.2	12.5	
	Heating	kW	8.0	8.8	10.0	11.0	12.5	13.5	
Power supply	PhV/Hz		1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	
Motor power input	W		83	83	133	133	133	133	
Air flow volume	m³/h		1180	1180	1860	1860	1860	1860	
	CFM		694	694	1095	1095	1095	1095	
Sound pressure level	dB(A)		39/37/35	39/37/35	40/38/36	40/38/36	40/38/36	40/38/36	
Main body	Dimension (WxDxH)	Outline	mm	840×840×240	840×840×240	840×840×320	840×840×320	840×840×320	840×840×320
		Package	mm	1103×963×325	1103×963×325	1103×963×409	1103×963×409	1103×963×409	1103×963×409
	Net weight/Gross weight		kg	30/38	30/38	38/46	38/46	38/46	38/46
Panel	Dimension (WxDxH)	Outline	mm	950×950×60	950×950×60	950×950×60	950×950×60	950×950×60	950×950×60
		Package	mm	1043×1028×130	1043×1028×130	1043×1028×130	1043×1028×130	1043×1028×130	1043×1028×130
	Net weight/Gross weight		kg	6.5/10	6.5/10	6.5/10	6.5/10	6.5/10	6.5/10
Connecting pipe diameter	Gas	inch(mm)	φ5/8(15.9)	φ5/8(15.9)	φ5/8(15.9)	φ5/8(15.9)	φ5/8(15.9)	φ5/8(15.9)	
	Liquid	inch(mm)	φ3/8(9.52)	φ3/8(9.52)	φ3/8(9.52)	φ3/8(9.52)	φ3/8(9.52)	φ3/8(9.52)	
Loading quantity	40'GP	set	100	100	88	88	88	88	
	40'HQ	set	114	114	90	90	90	90	

Compact 4-way Cassette

Model			GMV-Rh22T/NaA-K	GMV-Rh28T/NaA-K	GMV-Rh36T/NaA-K	GMV-Rh45T/NaA-K	
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	
	Heating	kW	2.5	3.2	4.0	5.0	
Power supply	PhV/Hz		1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	
Motor power input	W		50	50	50	50	
Air flow volume	m³/h		600	600	600	600	
	CFM		353	353	353	353	
Sound pressure level	dB(A)		47/41	47/41	47/41	47/41	
Main body	Dimension (WxDxH)	Outline	mm	570×570×230	570×570×230	570×570×230	570×570×230
		Package	mm	870×688×325	870×688×325	870×688×325	870×688×325
	Net weight/Gross weight		kg	16/25	16/25	18/27	18/27
Panel	Dimension (WxDxH)	Outline	mm	650×650×50	650×650×50	650×650×50	650×650×50
		Package	mm	733×673×117	733×673×117	733×673×117	733×673×117
	Net weight/Gross weight		kg	2.5/3.56	2.5/3.56	2.5/3.56	2.5/3.56
Connecting pipe diameter	Gas	inch(mm)	φ3/8(9.52)	φ3/8(9.52)	φ1/2(12.7)	φ1/2(12.7)	
	Liquid	inch(mm)	φ1/4(6.32)	φ1/4(6.32)	φ1/4(6.32)	φ1/4(6.32)	
Loading quantity	40'GP	set	301	301	301	301	
	40'HQ	set	344	344	344	344	